awing is ental to	TIAL NOTICE: This drawing and the de	signs, specifications and engineerin	ng information disclosed hereon are the property of E	5 berhard Manufacturing Company and are not t	b be disseminated or reproduced without express written consent	L.		REVISION HISTOR	
1 10	loaned in confidence and then only for cons Eberhard Manufacturing Company, Division	ideration of the matter disclosed her of the Eastern Company. 21944 Dr.	reon. In accepting loan of this drawing, recipient agro ake Road, Cleveland, Ohio 44149-9712 © 2013 EB	ees to keep it and the matter disclosed hereon ERHARD MFG. CO.	in confidence and not to use nor permit their use in any way		REV CONVE	DESCRIPTION RTED TO 3D	EN DATE 5596 3-22-1
Γ	PART NO.	A	AVAILABLE FINISH	MATERIAL					
	16832-48	48.00	(64)	1010 STEEL					
	16832-36	36.00	(64)	1010 STEEL					
ľ	16832-24	24.00	(64)	1010 STEEL					
ſ	16832-12	12.00	(64)	1010 STEEL					
	16832-22	22.25	(64)	1010 STEEL					
			-NYLON W	HEEL					
						J		Ø.31 ROE)
						<u> </u>			
		5							
		Ø.88-	\rightarrow						
			◄		A±.030				
			I						
						L			
		1.05							
			$ \mathbf{r} $		I	I			
			Ι						
									IER PRINT 1 OF 2
								EBERHARD MANU	
						THIS DOCUMENT IS IN ACC	ORDANCE WITH	DIVISIO THE EASTERI CLEVELAND, OHI	N COMPANY
						LINEAR MEASURE: INCH UNLESS OTHERWISE SPECIF TOLERANCES ARE AS FOLLO INCLES: <u>±2</u> ±		LOCK ROD W	ITH ROLLERS